



# Flight Line & Emergency Response Equipment



# Amerex Defense

PO Box 81 Trussville AL 35173-0081  
 PH (205)655-5703 • FAX (205)661-4111



## Model 600K 150 LB. HALON 1211 WHEELED FIRE EXTINGUISHER



- Brass, chrome plated operating valve
- 200 PSI Operating Pressure
- Heavy duty steel cylinder, carriage and hose hanger assembly
- Quick release 50 ft. discharge hose with brass/chrome plated ball type shut-off nozzle
- Pressure gauge protected by a stainless steel gauge guard
- Corrosion resistant lime/yellow polyurethane paint finish
- Large color coded mylar instruction labels
- 1 year limited warranty

SPECIFICATIONS	150 LB. HALON 1211
Model Number	600K
Agent	Halon 1211
Capacity (lbs.)	150
Shipping Weight (lbs.)	355 (filled)
Discharge Time (sec.)	48
Discharge Range (ft.)	30 - 40
Operating Temp Range	-65°F to +120°F
Hose Length (ft.)	50
Hose Diameter (in.)	.75
Wheels (Semi-pneumatic) (in.)	16 x 4
Height (in.)	59
Width (in.)	29
Depth (in.)	36

NSN: 4210-01-140-2233



# Amerex Defense

PO Box 81 Trussville AL 35173-0081  
PH (205)655-5703 • FAX (205)661-4111



## Model 775 150 LB. Novec™ 1230 WHEELED FIRE EXTINGUISHER



- Environmentally friendly 3M™ Novec™ 1230 Clean Agent (0 ODP - 1 GWP)
- Brass, chrome plated operating valve
- 125 PSI Operating Pressure
- Heavy duty steel cylinder, carriage and hose hanger assembly
- Lunette coupler for towing
- Quick release 40 ft. discharge hose with brass/chrome plated ball type shut-off nozzle
- Pressure gauge protected by a stainless steel gauge guard
- Corrosion resistant lime/yellow polyurethane paint finish
- Aluminum UL label with barcoded serial numbers
- Large color coded mylar instruction labels
- Operating temperature range: -40° to +120° F.
- 12 year prorated manufacturer's warranty

SPECIFICATIONS	150 LB. Novec™ 1230
Model Number	775
Agent	Novec™ 1230
Capacity (lbs.)	150
UL Rating	3A:80B:C
Shipping Weight (lbs.)	375 (filled)
Discharge Time (sec.)	22
Discharge Range (ft.)	30
Hose Length (ft.)	40
Hose Diameter (in.)	1.0
Wheels (Semi-pneumatic) (in.)	16 x 4
36" Rubberized Wheel Option	Available on Model 776R
Height (in.)	62
Width (in.)	29
Depth (in.)	42

NSN: 4210-01-610-6985





# Amerex Defense

PO Box 81 Trussville AL 35173-0081  
 PH (205)655-5703 • FAX (205)661-4111



## Model 688 50 LB. PURPLE K and 20 LB. CO<sub>2</sub> WHEELED FIRE EXTINGUISHER



### 50 lb. PURPLE K

- Stored Pressure Unit
- Less expensive up front cost alternative
- Agent is commonly used in hand held units for Tactical Wheeled Vehicles (i.e. HMMWV, MRAP)
- Less expensive alternative for Life Cycle Costing
- Brass fittings with swivels for ease of operation

SPECIFICATIONS	
Agent	PURPLE K
UL Rating	N/A
Capacity (lbs.)	50
Shipping Weight (lbs.)	174**
Discharge Time (sec.)	35
Discharge Range (ft.)	25-35
Operating Temperature Range	-65°F to +120°F
Hose Length (ft.)	25
Hose Diameter (in.)	.75
Wheels (Semi-pneumatic) (in.)	12.5 x 3.5
Height (in.)	46
Width (in.)	21.5
Depth (in.)	24

### 20 lb. CO<sub>2</sub>

- Stored Pressure Unit
- Less expensive up front cost alternative
- Rust free aluminum cylinders
- Less expensive alternative for Life Cycle Costing
- Warranty - 5 Years

SPECIFICATIONS	
Agent	CO <sub>2</sub>
UL Rating	10B:C
Capacity (lbs.)	20
Application	Hose & Horn
Shipping Weight (lbs.)	50.75**
Discharge Time (sec.)	19
Discharge Range (ft.)	3-8
Operating Temperature Range	-22°F to +120°F
Height x Width x Depth (in.)	30 x 13 x 8
FM Approved	YES
Coast Guard Approved	YES

\*\* Total shipping weight 225 lbs.

NSN: 4210-01-610-6986



# Amerex Defense

PO Box 81 Trussville AL 35173-0081  
 PH (205)655-5703 • FAX (205)661-4111



## Model 691 125 LB. PURPLE K and 20 LB. CO<sub>2</sub> WHEELED FIRE EXTINGUISHER



### 125 lb. PURPLE K

- Stored Pressure Unit
- Less expensive up front cost alternative
- Agent is commonly used in hand held units for Tactical Wheeled Vehicles (i.e. HMMWV, MRAP)
- Less expensive alternative for Life Cycle Costing
- Brass fittings with swivels for ease of operation

SPECIFICATIONS	
Agent	PURPLE K
UL Rating	N/A
Capacity (lbs.)	125
Shipping Weight (lbs.)	344*
Discharge Time (sec.)	48
Discharge Range (ft.)	30-40
Operating Temperature Range	-65°F to +120°F
Hose Length (ft.)	50
Hose Diameter (in.)	.75
Wheels (Semi-pneumatic) (in.)	16 x 4
Height (in.)	53.5
Width (in.)	28
Depth (in.)	40

### 20 lb. CO<sub>2</sub>

- Stored Pressure Unit
- Less expensive up front cost alternative
- Rust free aluminum
- Less expensive alternative for Life Cycle Costing
- Warranty - 5 Years

SPECIFICATIONS	
Agent	CO2
UL Rating	10B:C
Capacity (lbs.)	20
Application	Hose & Horn
Shipping Weight (lbs.)	50.75*
Discharge Time (sec.)	19
Discharge Range (ft.)	3-8
Operating Temperature Range	-22°F to +120°F
Height x Width x Depth (in.)	30 x 13 x 8
FM Approved	YES
Coast Guard Approved	YES

\* Total shipping weight 395 lbs.



# Amerex Defense

PO Box 81 Trussville AL 35173-0081  
 PH (205)655-5703 • FAX (205)661-4111



## Model 781/782/783/784 VEHICLE MOUNTED EXTINGUISHER

### FEATURES

- **Truck Mountable**
- **Easy to Use & Recharge**
- **4 lbs/Second Flow Rate**
- **Quick Flame Knock-Down**
- **Low Profile Design**
- **Stored Pressure Design**

The Amerex Models 781, 782, 783 and 784 are designed for Military rescue applications. The system allows any vehicle to become a "Portable Fire Truck". The extinguisher was designed to be placed in the rear hatch of a HMMWV but can also be utilized in numerous other types of Military convoy vehicles.



Shown with Vehicle Access Tray

### SPECIFICATIONS

Agent	ABC Dry Chemical	Sodium Bicarbonate	Purple K	Liquid Agent
Model No.	781	782	783	784
Size	150 (lbs.)	150 (lbs.)	150 (lbs.)	15 (gal.)
Height (in.)	24"	24"	24"	24"
Width (in.)	22"	22"	22"	22"
Depth (in.)	38"	38"	38"	38"
Discharge Time (sec.)	36	36	36	50
Hose Length (ft.)	40	40	40	40
Range (ft.)	40 - 50	45 - 50	40 - 50	40 - 50
Effective Range (ft.)	15 - 20	15 - 20	15 - 20	15 - 20
Operating Pressure (psi)	240	240	240	240
Operating Temperature Range	-40°F to +120°F	-40°F to +120°F	-40°F to +120°F	-40°F to +120°F

\* UL Listed Hose Line Application (Red Painted Only)



# Amerex Defense

PO Box 81 Trussville AL 35173-0081  
 PH (205)655-5703 • FAX (205)661-4111



## Model B674 150 LB. HALOTRON® I WHEELED FIRE EXTINGUISHER



- Brass, chrome plated operating valve
- 150 PSI Operating Pressure
- Heavy duty steel cylinder, carriage and hose hanger assembly
- Quick release 50 ft. discharge hose with brass/chrome plated ball type shut-off nozzle
- Pressure gauge protected by a stainless steel gauge guard
- Leaves no residue
- 5 year limited warranty

SPECIFICATIONS	150 LB. HALOTRON® I
Model Number	B674
Agent	Halotron® I
UL Rating	10A:120B:C
Capacity (lb.)	150
Shipping Weight (lb.)	512 (filled)
Discharge Time (sec.)	31
Discharge Range (ft.)	30 - 45
Operating Temp Range	-40°F to +120°F
Hose Length (ft.)	50
Hose Diameter (in.)	.75
Wheels (Semi-pneumatic) (in.)	16 x 4
Height (in.)	64
Width (in.)	30
Depth (in.)	42

NSN: 4210-01-609-8709





## Amerex Defense

P.O. Box 81  
Trussville, AL 35173  
Ph: (205) 655-5703  
Fax: (205)-661-4111

[www.amerex-defense.com](http://www.amerex-defense.com)  
[defensesales@amerex-fire.com](mailto:defensesales@amerex-fire.com)



ISO 9001 - Quality  
ISO 14001 - Environmental  
OHSAS 18001 - Safety  
**CERTIFIED FIRM**

For more information please contact:

Amerex Corporation makes every attempt possible to provide the most current and updated information. Information contained within this brochure is deemed to be as accurate as possible as of the printing date. Routine changes to products, codes and standards, and warranties subsequent to this printing will supersede printed information. Please contact Amerex Corporation for any revisions, updates, or product changes.